


PP400

Technical Specifications

GB

Version 1.0 February 2006



FEATURES

- ▲ Converts your phono signal to a line level signal
- ▲ State-of-the-art phono preamp to accommodate magnetic pickups
- ▲ Ultra low-noise audio operational amplifiers offer outstanding sound performance
- ▲ Dedicated RCA and 1/4" output connectors
- ▲ DC 12-Volt adapter included
- ▲ High-quality components and exceptionally rugged construction ensure long life
- ▲ Conceived and designed by BEHRINGER Germany

SPECIFICATIONS

INPUT

Type	RCA connector
Impedance	approx. 47 k Ω
Max. input level	-23.5 dBV @ 1kHz

OUTPUT

Type	RCA and 1/4" TRS, stereo connectors
Impedance	approx. 50 Ω
Max. output level	+11.5 dBV @ 1 kHz

SYSTEM SPECIFICATIONS

Frequency response	RIAA
THD	0.06% typ. @ -40 dBu/1 kHz
Gain	35 dB
Signal-to-noise ratio	68 dBu @ 0 dBu, A-weighted
Input sensitivity	5.3 mV @ 1 kHz

POWER SUPPLY

Mains connection	external power supply, 12 V DC / 150 mA
Mains voltage	
USA/Canada	120 V~, 60 Hz
China/Korea	220 V~, 50 Hz
U.K./Australia	240 V~, 50 Hz
Europe	230 V~, 50 Hz
Japan	100 V~, 50 - 60 Hz
Power consumption	approx. 1.5 W

DIMENSIONS/WEIGHT

Dimensions (H x D x W)	approx. 1 1/4" x 4" x 2 1/2" (approx. 32 mm x 103 mm x 64 mm)
Weight	approx. 0.40 lbs (0.180 kg)

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

Technical specifications and appearance subject to change without notice. The information contained herein is correct at the time of printing. The names of companies, institutions or publications pictured or mentioned and their respective logos are registered trademarks of their respective owners. Their use neither constitutes a claim of the trademarks by BEHRINGER® nor affiliation of the trademark owners with BEHRINGER®. BEHRINGER® accepts no liability for any loss which may be suffered by any person who relies either wholly or in part upon any description, photograph or statement contained herein. Colours and specification may vary slightly from product. Products are sold through our authorised dealers only. Distributors and dealers are not agents of BEHRINGER® and have absolutely no authority to bind BEHRINGER® by any express or implied undertaking or representation. No part of this manual may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording of any kind, for any purpose, without the express written permission of BEHRINGER Spezielle Studioteknik GmbH. BEHRINGER® is a registered trademark.

ALL RIGHTS RESERVED. © 2006 BEHRINGER Spezielle Studioteknik GmbH,
Hanns-Martin-Schleyer-Str. 36-38, 47877 Willich-Münchheide II, Germany.
Tel. +49 2154 9206 0, Fax +49 2154 9206 4903

MICROPHONO

www.behringer.com

