Superlux


E205 STUDIO CONDENSER MICROPHONE


Description

Designed for critical home/project/professional studio applications and live performances, this side-address supercardioid studio condenser microphone delivers exceptional detail and low noise. Along with its rugged construction and high-performance specifications, the E205 provides an exceptional level of consistency from model to model.

Features

- Large diaphragm for smooth, natural sound and low noise
- High SPL handling and wide dynamic range provide unmatched versatility
- Supercardioid polar pattern reduces pickup of sounds from the sides and rear, improving isolation of desired sound source.





Included



Pouch








HM85 pivoting stand mount



Specifications	
Туре	Back Electret Condenser
Polar Pattern	Supercardioid
Frequency Response	30 - 18,000 Hz
Sensitivity	-38 dBV / Pa (12.6 mV)
Output Impedance	200 Ω
Min. Load Impedance	1,000 Ω
S/N Ratio	72 dB
Equivalent Output Noise	< 22 dB
Max. SPL	> 135 dB
Dynamic Range	> 113 dB
Power Requirements	12 – 52 V , 3.5 mm
Finish	Black
Connector	XLR3M
Dimensions	Ø54 × 150 mm
	(Ø2.13" × 5.9")
Net Weight	400 g (14.1 oz)

E205 Frequency Response (Superardioid)







Devices with this label are subject to the current EU directive on waste electrical and electronic equipment (WEEE directive) and may not be disposed of with household waste, but only through a suitable waste disposal company. Ask your local government or your specialist dealer about your options for proper disposal.

