DATA SHEET



F23





GLOBAL TRUSS F23 TRUSS SYSTEM

Global Truss represents the highest quality and reliability.

The Global Truss F23 is a 3-point truss system. This provides optimum volume and carrying capacity for its construction size and a tube diameter of only 35mm. This system is connected via a special conical connector system, which is joined together to a complete form fit by means of a copper hammer, creating optimal traction.

The Global Truss F23 finds application in trade fairs and shops, as well as in the event industry in general. It is also characterised by a minimum transport volume and the special lightweight design.

The conical connectors are of course included in the scope of delivery special designs and powder coatings can be carried out at short notice.

Global Truss has the largest truss storage worldwide and is permanently able to deliver all systems. Furthermore, Global Truss is the only truss manufacturer with its own coupler and hook range tested by "TÜV" and "DIN".

TECHNICAL DATA

Pipe diameter main pipe: 35mm Wall thickness: 1,6mm

EN AW-6061 T6/T4 Material:

Snake brace: 8,8mm Conical connectors included in scope of delivery







INCLUSIVE

LOAD TABLE





Span	Unifor distrik	
m	kg/m	
2,00	65,00	
3,00	42,00	
4,00	31,00	
5,00	24,00	
6,00	20,00	
7,00	17,00	
8,00	14,00	
9,00	12,00	
10,00	11,00	

✓ Center point l	
kg	
129,00	
127,00	
124,00	
121.00	

118.00

100,00

86,00

74.00

65.00

Deflection

cm

1,07

1,86

2,96

4,43

6.32

cm
0,11
0,36
0,85
1,65
2,83
3,93
5,22

6,71 8,42

61.00

59.00

58,00

57,00

55.00

48.00

1,42

2,45

8.17

10.23

40.00

39.00

39,00

38,00

37,00

33.00

Deflection

cm

0,29

0,68

1,33


2,29

3,63

5,41

7,68





27.00

Deflection

10.12

The weight of the truss is considered in the load table



